

CLIP-TEC













Solutions builder

Winning your time





• Quick and easy to set up with a new clip system

Perfect for installation in tight space or without back access

No need a clamping range for the body

Wider clamping range

Tool free assembly

Different wall thickness: 1,5 to 3 mm



MATERIAL

Body and cap nut: PA6

Sealing: neoprene

O ring: nitrile

■ Temperature: -40 °C / +100 °C

IP protection: IP65 Other RAL available

Metric equivalent	Thread (T)	Part Number			Sealing	Overall cable diameter (D)		u		Packing
		RAL7035	RAL 7001	RAL 9005	Sealing	Min	Max	"		racking
	16	F7021612	F7021610	F8021605	Standard	3,5	10,0	22,0	29,0	50
	16	F7021641	F7021653	F8021641	Reduced	2,0	7,0	22,0	29,0	50
	20	F7022053	F7022061	F8022054	Standard	7,0	12,0	24,0	30,0	50
	20	F7022062	F7022070	F8022061	Reduced	3,0	9,0	24,0	30,0	50
	25	F7022506	F7022514	F8022503	Standard	9,0	18,0	33,0	39,0	25
	25	F7022541	F7022553	F8022541	Reduced	7,0	16,0	33,0	39,0	25



HEADQUARTERS, PLANT

FRANCE

25, rue Théophile Somborn F-57220 BOULAY-MOSELLE

3 +33 (0)3 87 79 20 22

ITALY

Viale Cesar Battisti, 43 I-24047 TREVIGLIO BG 9 +39 348 3860 212

SALES DEPARTMENT

FRANCE

EXPORT

(2) +33 (0)3 87 79 39 81 +33 (0)3 87 79 39 80 **©** +33 (0)3 87 79 35 63 +33 (0)3 87 79 35 48

M25